



LED Flood Light

TL-SL291



Feature:

- * Strobe: fast electronic strobe 0-20Hz.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * Display menu: 0802LCD operation panel, support the invocation of various scenes; built-in programs can be directly invoked and executed.
- * Temperature control: with intelligent temperature protection function to ensure the LED lifespan.

Specifications:

Model	TL-SL291
Input voltage	AC 110-240V 50/60Hz, 80W
Light source	7×12W LED(4IN1)
Average lifespan	50000H
Beam angle	15°
Fixture connection	Three-core signal line IN/OUT and power line IN/OUT
Control mode	DMX512, built-in self-propelled program, master-slave online mode, support RDM and program online update
Channel	3/4/7 channels
Fixture material	Aluminum alloy die-casting structure
Protection class	Fireproof V-1, protection IP30
Fixture size (L×W×H)	218×167×279mm
Net weight	4.5kg
Working temperature	-20°C~40°C