



LED Flood Light

TL-SL292



Feature:

* Strobe: fast electronic strobe 0-20Hz.

* Color mixing: RGBWA+UV (red, green, blue, white, amber and UV) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.

* Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.

* Display menu: 0802LCD operation panel, support the invocation of various scenes; built-in programs can be directly invoked and executed.

* Temperature control: with intelligent temperature protection function to ensure the LED lifespan.

Specifications:

| | |
|----------------------|--|
| Model | TL-SL292 |
| Input voltage | AC 110-240V 50/60Hz, 80W |
| Light source | 7×12W LED(6IN1+UV) |
| Average lifespan | 50000H |
| Beam angle | 15° (25/45° optional) |
| Fixture connection | Three-core signal line IN/OUT and power line IN/OUT |
| Control mode | DMX512, built-in self-propelled program, master-slave online mode, support RDM and program online update |
| Channel | 3/6/9 channels |
| Fixture material | Aluminum alloy die-casting structure |
| Protection class | Fireproof V-1, protection IP30 |
| Fixture size (L×W×H) | 218×167×279mm |
| Net weight | 4.5kg |
| Working temperature | -20°C~40°C |