



Feature

- * Strobe: Independent electronic strobe 1-25Hz.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustable), built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * Display menu: support the invocation of various scenes; built-in programs can be directly invoked and executed.
- * Features: Cast aluminum shell, high light efficiency, uniform light mixing, stable performance, equipped with 2-meter long power cord and signal line.
- * Fixture connection: three-core signal line IN/OUT power line IN/OUT.
- * Scenes: 20 built-in scenes that can be edited independently. 2 operating modes: constant speed and variable speed. The switching speed between scenes can be customized.
- * Dynamic effects: Built-in 17 different dynamic effects, supporting RGB (red, green and blue) three-color mixing or running dynamic effects.
- * Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power will be intelligently reduced.
- * Automatic color correction system: ensure stable and consistent color and color temperature

Specification

| | |
|----------------------|---|
| Input voltage | AC 110-240V 50/60Hz , 350W |
| Light source 1 | 22×20W LED(RGBW) |
| Light source 2 | 54×0.5W LED(RGB) |
| Average lifespan | 50000H |
| Color temperature | 2800K ~ 10000K linear adjustment |
| Beam angle | 20° |
| Control mode | DMX512, built-in program self-propelled, master-slave online mode, Art-net Ethernet data interface, supports RDM protocol and program online update function. |
| Channel | 17/12/10/6 channel |
| Fixture material | Cast aluminum housing |
| Protection class | Fireproof V-1, protection Ip30 |
| Fixture size (L×W×H) | 297×246×381mm |
| Package size (L×W×H) | 580×300×485mm |
| Gross weight | 18.2kg (2PCS) |
| Net weight | 6.8kg |