



# Pattern Light

## TL-LT202A



### Feature:

- \* Color wheel: one 5+1 fixed color wheel, two-way stepless rotation, magnet positioning, color index, half-color and other functions.
- \* Gobo wheel: 1 rotatable gobo wheel, 4 gobos; support pattern positioning, rotation, dithering, etc.
- \* Dimming: 0-100% linear adjustment.
- \* Strobe: electronic strobe, 0-25 times/sec (built-in pulse stroboscopic effect).
- \* DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- \* Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced
- \* LCD blue screen display, including the lamp usage time, software version number, etc.

### Specifications:

|                      |   |
|----------------------|---|
| Model                | TL-LT202A   |
| Input voltage        | AC 110-240V 50/60Hz, 240W   |
| Light source         | A 200W White Light LED OSRAM chip   |
| Average lifespan     | 50000H  |
| Color temperature    | 7500K   |
| Beam angle           | 30°/45°/60° /75°(optional)  |
| Control mode         | Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function |
| Operation mode       | DMX mode, user program mode, built-in program mode  |
| Channel              | 7/9 channels  |
| Fixture material     | High-strength die-cast aluminum alloy + copper tube radiator + a waterproof fan to assist heat dissipation  |
| Protection class     | IP67  |
| Working temperature  | -20°C~45°C  |
| Fixture size (L×W×H) | 230×180×367mm   |
| Package size (L×W×H) | 270×250×455mm   |
| Gross weight         | 9.3kg   |
| Net weight           | 8.3kg   |