



Feature

- * Power supply: 1.5kw/380V/3P/50Hz
- * Control: The electric hoist is equipped with standard connecting cables and CE-type connectors, and has built-in adjustable upper and lower stroke limit devices.
- * Housing: Rainproof high-strength deep-drawn steel structure.
- * Transmission device: The gear is permanently in a lubrication system, which makes the gear run more smoothly, cools down, lubricates, and prolongs the service lifespan.
- * Lifting chain: 7×22mm, G100 galvanized lifting chain, chain length 15 meters, T level: breaking strength 800 N per square millimeter, and the safety factor is Grade 8.
- * Motor: The insulation class is Class F. The maximum allowable temperature is 155 °C, the winding temperature rise limit reaches 100 °C, and the performance reference temperature reaches 100 °C.
- * Chain guide device: The unique five-hole lifting sprocket makes the chain lift in a balanced manner; nylon chain guard: as long as the chain is not knotted, it can run smoothly.
- * Reliability: The hoist is equipped with a patented overload protection clutch, which can protect the safety of the operator and the product from damage when overload occurs.
- * Safety: Lifetime maintenance, and related accessories and technical support are provided.
- * Load: 1000kg, lifting speed: international standard 6.8m/min
- * Equipment weight: about 67kg