



## Feature

- \* Optics: two sets of high-precision glass optical lens (3-layer coating film).
- \* Zoom: any angle optional
- \* Strobe: 1-25 times/sec strobe frequency, with synchronous strobe mode, adjustable speed.
- \* Display interface: a 3.5-inch widescreen LCD interface in Chinese and English, the hierarchical menu structure and graphical interface are user-friendly.
- \* Intelligent heat dissipation: adopt wind direction drainage and intelligent temperature monitoring technology; according to the temperature of different parts of the light, the cooling fans in different parts are automatically started to cool the light components down.
- \* Dimming curve: with 4 kinds of dimming curves to adapt to different occasions.
- \* Quick replacement of lens modules: The lamp body and optical module are designed with a quick lock device, which is convenient for debugging and replacement of various optical modules.

## Specification

<b>Input voltage</b>	AC110V-240V 50/60Hz , 650W
<b>Light source</b>	1pcs 500W white LED
<b>Average lifespan</b>	20000H
<b>Color temperature</b>	5600K, color rendering index Ra≥95
<b>Beam angle</b>	18-43°
<b>Control mode</b>	DMX512 protocol, support RDM protocol and program online update function; (Art-net Ethernet data interface, DMX wireless function optional)
<b>Channel</b>	5 channels
<b>Fixture material</b>	High temperature resistant plastic + molded alloy material
<b>IP rate</b>	Ip20
<b>Fixture size (L×W×H)</b>	340×240×506mm
<b>Package size (L×W×H)</b>	400×375×525mm
<b>Gross weight</b>	18.0kg
<b>Net weight</b>	15.5kg