



Feature

- * Projection angle: Support four-corner adjustment, adjust the four corners of the picture until the appropriate position
- * Automatic startup: support automatic startup, no need for manual startup, easy to use
- * All-round installation: 720° all-round installation, simple and easy installation
- * Multimedia playback: built-in video and picture playback function
- * Control mode: RJ-45 (TCP/IP control), compatible with DMX512, capable of overall linkage
- * Input port: 1 HDMI USB TypeA2 (waterproof interface)
- * Control port: 1 wired LAN RJ45 (waterproof interface)
- * Output port: audio (optional)
- * Interactive effect: built-in interactive effect device (optional support available)
- * Preset effects: built-in interactive fusion (optional multiple interactive effects)
- * Splicing structure: edge blending, splicing (optional support available)

Specification

Input voltage	AC 220V±10% , 50/60Hz , 500W
Display chip	Texas Instruments DLP 0.65 DMD chip
Resolution	1920×1080
Visual brightness	6500 lumens
Contrast	100,000:1
Display color	16.7 million colors
Throw ratio	0.8:1 (optional 0.52:1, 0.75:1, 1.1:1)
System solutions	RK3399, Android system, customizable PC architecture system solution
Running memory	4GB
Hard drive memory	64GB
Image ratio	16:9 compatible with 16:10/4:3
Working noise	38dB(TBD)
Average life span	25000H
Protection level	Ip65
Material	All aluminum alloy shell
Product size (L×W×H)	470×370×391mm
Packaging size (L×W×H)	560×450×377mm
Gross weight	23kg(1PCS)
Net weight	20.4kg