



Water Effect Light

TL-LT104A



Feature

- * Color: 3*20W (RGBW) red, green, blue and white light, RGBW color mixing.
- * Function: 1 water pattern glass column, independent rotation, forward and backward stepless rotation, and adjustable speed; dynamic starry sky effect, starry sky forward and backward rotation, and adjustable speed control, light and dark linear transformation.
- * Dimming: 0-100% linear adjustment.
- * Strobe: electronic strobe, 0-25 times/second (built-in pulse strobe effect).
- * DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- * Over-temperature protection function: Built-in NTC temperature control function, when the LED is overheated, it intelligently reduces the output power of the LED.

Specification

Model	TL-LT104A
Input voltage	AC 110-240V 50/60Hz, 80W
Light source	3 OSRAM 20W (RGBW) red, green, blue and white LED + imported chip 10W laser diode, white light module
Average lifespan	20000H
Color temperature	7500K
Beam angle	22.5° x100°
Control mode	Comply with the international standard DMX512 signal control protocol, 3-pin (optional 5-pin) DMX512 signal interface, master-slave synchronous control mode, support RDM protocol
Operation mode	DMX mode, user program mode, built-in program mode
Channel	7/11 channels
Fixture material	High-strength extruded aluminum + die-cast aluminum alloy end cap
Protection class	Ip67
Working temperature	-20°C ~ 45°C
Fixture size (L×W×H)	722×140×174mm
Package size (L×W×H)	790×210×250mm
Gross weight	5.7kg
Net weight	4.8kg