



# Water Effect Light

## TL-LT105



### Feature:

- \* Color: 1 color wheel: 6 colors + cooling film + white light, half-color effect, variable-speed two-way rainbow effect, step/linear color conversion is optional.
- \* Function: 2 water gobo wheels, independent rotation, two-way stepless rotation; realize the natural water flow effect with the color changing.
- \* Dimming: 0-100% linear adjustment.
- \* Strobe: electronic strobe, 0-25 times/sec (built-in pulse stroboscopic effect).
- \* Spot: the light spot changes with high-speed electric linear zooming.
- \* DMX512 port program update, convenient and fast software update via DMX data cable.
- \* Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power will be intelligently reduced.
- \* Full color TFT screen display, including the lamp usage time, software version number, etc.

### Specifications:

Input voltage	AC 110-240V 50/60Hz, 350W
Light source	300W white light LED
Average lifespan	50000H
Color temperature	7000K
Beam angle	25°~50° electric adjustment
Control mode	Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function
Operation mode	DMX mode, user program mode, built-in program mode
Channel	9 channels
Fixture material	High temperature resistant aluminum alloy + high temperature resistant/UV resistant engineering plastic + copper tube radiator + 2 waterproof fan to assist heat dissipation
Protection class	IP67
Working temperature	-20°C~45 °C
Lamp size (L×W×H)	520×346×429mm
Packing size (L×W×H)	405×355×625mm
Gross weight	21KG
Net weight	18.9KG